

R*TEL

205, 215

Single-Use Temperature
Data Loggers

Durability Meets Pharma-Grade Precision



Hard-case protection with advanced temperature and humidity monitoring for sensitive pharma products.

RTEL 205/215 Data Loggers from RTE are engineered for demanding routes and sensitive pharmaceuticals. Their durable design delivers accurate, audit-ready temperature monitoring plus protection against rough handling applications from fill and finish through final mile delivery.

Both models feature four programmable alarms, NIST-traceable calibration, and secure PDF/CSV reporting. RTEL 215 adds relative humidity logging for products vulnerable to moisture shifts. —trusted by pharma teams worldwide.



Simple to Use

One-touch start/stop
USB / Plug n' Play



3-Point NIST

Traceable calibration
ensures accuracy



High Capacity

Up to 33,000 time-
stamped data points



Programmable

Customize alarm & start
delay settings



Wide Temp Range

-30°C—70°C
(-22°F—158°F)



FDA Compliant

Meets 21 CFR Part 11
compliance standard

For over 40 years, RTE has pioneered temperature monitoring in refrigerated transport—including RTEL, the industry's first digital data logger for perishable shipments, launched in 1994.

RTE

Technical Specifications



RTEL 205

Single-Use
Temperature Logger

- ✓ Check Min, Max, Avg Temp during transit
- ✓ View screen at any angle
- ✓ Hard-Case Format



RTEL 215

Single-Use
Temperature & RH
Logger

- ✓ Adds Relative Humidity Monitoring

RTEL 205 / 215

Notification Type	LCD Display - Recording, OK/Alarm, Start Delay, Avg/Max/Min Temperatures
Battery Life	up to 2 years (1yr storage / 1yr in-use life) @ 25°C & 5 min logging interval
Measurement Range	-30 °C ~ 70 °C
Measurement Accuracy	± 0.5°C @-10~40°C, ± 0.8°C @-30 ~-10°C & 40~70°C ±3%RH@20-80%RH,±4%RH@other (215 Only)
Resolution	0.1°C 0.1%RH (215 Only)
Alarm Limits	(4) Two High / Two Low Programmable Alarms - Customize alarm threshold and delays
Logging Interval	1 minute - 24 hours (Default 10 minutes)
Storage Capacity	205: up to 33,000 data points for single PDF or CSV report / <25,000 for combined report 215: up to 25,000 data points for single PDF or CSV report / <18,000 for combined report
Report Format	PDF / CSV / Combined PDF&CSV (Optional Configuration)
Start Delay	0 minutes - 24 hours (Default 15 minutes)
Start Mode	Manual Start
IP Rating	IP65
Battery Type	3.0V CR2032
Connection	USB2.0
Dimensions	105x40x10mm
Weight	30g
Product Certifications	CE, EN12830:2018, RTCA/DO-160G (Aviation Safety Directive), RoHS




Rugged Design
Durable IP65-rated protective case

Other Solutions

RTEL 100

Single-use
Temperature Indicator


Simple, economical, and delivering actionable insights that ensure safety and compliance.



RTEL 201

Single-use
Temperature
Data Logger

A value-based solution for asset temperature logging with easy-to-read LCD display and USB report access.



Request a sample logger today.
Because compliance starts with confidence.

RTE